

PVC fast fix ducting system

# **Physical specification**

All measurements in millimetres unless otherwise indicated

# Ducting Material: Rigid PVC






- Designed to save time and improve safety by allowing installations to be completed internally
- Seal between external grille and duct provides watertight seal

# Installation

Push through 117mm diameter core drilled hole with external grille situated to outside of building.

#### The discount group applied to all Fastfix ancillaries is F6

Fastfix models and prices		
Brown external grille	FF100B	£27.41
White external grille	FF100W	£27.41





# **Physical specification**

All measurements in millimetres unless otherwise indicated

Materials: Rigid black PVC to BS4514







## **Features and benefits**

- Efficient one-visit system designed to save installation time and storage cost
- Integral screw holes ensuring rapid fixing and secures fan direct to duct
- > No need to drill and plug fixing holes
- Simply cut on-site to length required for installation

# Installation

Cut duct to the length required. Install and make good. Fix fan and grille direct to duct.

# ED1 hole size required:

Ø 125mm

ED150 hole size required: Ø 170mm

#### luirea

### The discount group applied to all Easyfix ancillaries is F6

Easyfix models and prices	
Ø 100mm, length 375mm ED1	£8.35
Ø 150mm, length 375mm ED15	<b>0</b> £12.13