

# Ei1025



## Temperature, Humidity and CO2 Environmental Sensor



- Condensation, Damp, Mould and Indoor Air Quality
- Easy to install and manage
- Gather data on indoor environmental conditions
- Suitable for wall and ceiling mounting
- 10-year lithium battery
- Connection to Ei1000G SmartLINK Gateway required to extract data



### Technical

<b>Sensor Type</b>	Temperature, Humidity and CO2	<b>RF Frequency (MHz)</b>	868.2
<b>RF Range (m)</b>	>100 in free air	<b>Battery Type</b>	Lithium primary
<b>Technologies</b>	HomeLINK		

### Dimensions & Weights

<b>Depth (mm)</b>	36	<b>Height (mm)</b>	105
<b>Width (mm)</b>	105	<b>Product weight (kg)</b>	0.081
<b>Packaged weight (kg)</b>	0.134		

### Approvals & Warranty

<b>Certification/Approvals</b>	EN 300 220-1, EN 300 220-2, EN 301 489-1, EN 301 489-3 & EN 62368-1	<b>Warranty</b>	5 year warranty
--------------------------------	---	-----------------	-----------------

### Environmental

<b>Humidity Range (%)</b>	15-95	<b>Temperature Range (°C)</b>	-10 to 40
---------------------------	-------	-------------------------------	-----------