

Luminaires | Downlights

Uni-FitCS™ Colour Switchable 23W Fixed Polycarbonate Downlights

AU-DL23CS



Photometrics

Wattage	23
Lumens	2500 - 2700
Lm/W	117
Beam Angle	100
Colour Temperature	3000 / 4000 / 6500
Ra	650
SDCM	<10
UGR19	No

Product Features

Brand	Aurora
IP Rating	IP44
IK Rating	IK02
L70 Hours	L70 40,000
Lifetime Class	B50
SKU Type	Non Dim
Dimmable	No
Warranty	5 Years

Country of Origin	CN
-------------------	----

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.9
Surge Protection (kV)	1500
Protection Class	class 2
Frequency (Min) Hz.	50HZ
Frequency (Max) Hz.	60HZ
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40
Glow Wire Test (°C)	No

Physical Attributes

Height (mm)	65
Overall Diameter (mm)	200
Lamp Base	LED
Cutout Diameter Max. (mm)	170
Product Weight (KG)	0.395
Material	Polycarbonate
Optic Material	Polycarbonate
Diffuser	Opal
Finish Colour	White

Features

Marketing Feature 1	Colour switchable between 3000/4000/6500K
Marketing Feature 2	Compact integrated driver for easy installation and shallow ceiling voids
Marketing Feature 3	IP44 rated
Marketing Feature 4	TP(a) rated
Marketing Feature 5	3 year warranty