



GENBAY EMERGENCY CONVERTER

Emergency Converter Manual & Self Test

FEATURES

IP rating	IP65
-----------	------

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	5°C - 35°C
Weight	697g
Double Insulation	Yes
Inrush Current	3.1A 1ms
Construction Material	Polycarbonate
Electric Class (1, 2, 3)	II
Battery	6.4V 6000mAh
Install Connector Type	Push-fit terminals 0.75 - 2.5mm ²
UK Building Regulations	Part P & L
Connection Output	Push-fit terminals

PHOTOMETRICS @ 25°C

Product code	Finish	EM lm
HBGEMC1MS	Black	1400

WIRING INFORMATION

Type of Wiring Required	Parallel
Input Cable Type	Push-fit terminals 0,75 - 2,5mm ²
Output Cable Type	Push-fit terminals 0,75 - 2,5mm ²

Self Test or Manual Test Self-test and Manual-test switchable (Self-test is preset)

LiFePO4 provides long operational life

EM 3h A minimum of 3 hours of emergency lighting

WARRANTY

Warranty	3 years
Battery Warranty	3 years

FEATURES & BENEFITS

IP65 rated enclosure

Loop in and loop out tool-less wiring