

Girona Panel Heater (White) - Series B



Technical Details

Controls	Digitally controlled, Electronic Thermostat accurate to ($\pm 0.2^{\circ}\text{C}$). Setpoint range (7-30°C) Timer modes: 7 Day Programmable User Timer, Out All Day, Home All Day Continuous heat modes: Eco, Manual, Frost Protect. Additional modes: Away, Boost, Setback, Runback
Controller UI	<ul style="list-style-type: none"> Graphical display with RGB backlight Capacitive buttons with audio feedback User replaceable battery (Coin-Type)
Controller Functions	<ul style="list-style-type: none"> Open window detection Adaptive-start, Advance time period Bluetooth for software updates Child Lock & Heater Lock (PIN-based)
Construction	<ul style="list-style-type: none"> Durable epoxy-polyester powder coated steel casing with louvered upward facing grille Advanced controls with cap-sense technology for total flexibility of heating
Element	Compact, finned, mineral filled sheathed element
Installation	<ul style="list-style-type: none"> 1 H-frame wall bracket for easy fixing
Safety	<ul style="list-style-type: none"> Thermal cut-out. Auto reset type Overheat detection
IP Rating	IP24
Battery Back-up	CR2032 Lithium Manganese Dioxide 3V coin cell battery to backup real time clock. Battery life > 5 years.
Supply	1.3 metres fitted, 3 core for fused spur installation, 1/N/PE ~230-240 V, 50Hz Class I, with earth wire
Colour / Finish	Metal Chassis, Air Outlet Grille & Control Moulding - Traffic White (RAL 9016)

Warranty & Approvals

Approvals	CE, BEAB
Warranty	2 Years
Country of Origin	United Kingdom
Manufacturer	Glen Dimplex Heating & Ventilation (GDC Group Ltd)

Product Description


GFPWE features intuitive user controls, allowing the programming of multiple 7-day timer profiles via a backlit LCD display and capacitive buttons

Key Features

- Modern panel design with louvered upward facing grille for optimum heat circulation
- Customisable heating with four time and temperature settings per day.
- Adaptive start pre-heating and open window detection auto-shutdown
- Slimline design that covers traditional panel heater fixing marks
- Aesthetics to compliment storage heater ranges
- Smartphone app controllable via the Dimplex Control system*

**Requires additional hardware, sold separately. A Dimplex Hub and RFM 'Radio Frequency Module' device are required for this product to connect to the Dimplex Control system and be controlled via the Dimplex Control smartphone app*

Dimensions



**Please note correct product orientation is with controller facing top right side only*

Model/Item No. (EAN-Code 5011139+Item No.)	090850	GFP050WE	090867	GFP075WE	090874	GFP100WE	090881	GFP150WE	090898	GFP200WE
Output (kW)	0.50		0.75		1.00		1.50		2.00	
Height 'D' (mm)	565		565		565		565		565	
Width 'C' (mm)	530		530		700		770		940	
Depth 'E' (mm)	107		107		107		107		107	
Weight (Kg)	13.4		13.4		16.9		18.6		22.1	
Packaging Details										
Height (mm)	670		670		670		670		670	
Width (mm)	590		590		764		837		1000	
Depth (mm)	182		182		182		182		182	
Packed Weight (Kg)	15.1		15.1		19		20.7		24.4	
Ti	10		10		7		7		6	
Hi	3		3		2		2		2	
Pallet Quantity (2.4m high)	30		30		14		14		12	