

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

741XLEDITB100

Hartland | HARTLAND RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

Item Image	Wiring	Dimensions	
• • •	NO IMAGE	HEILIGUE HARTLAND ILLEUTE LEDTB100 2 Way Dimmer	
Primary Range	Hartland		
Insert Type	l gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer		
Insert Colour	Satin Steel		
EAN13 Barcode	5017504079307		
Commodity Code	85365015		
Luckins TSI	403373635		
Dimensions(Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm		
Weight	112 GR		
Switched Poles	Single		
Current Rating	0.4A		
Voltage	230V AC		
Maximum Load	5-100W (10 LED Lamps MAX)		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Terminal Capacity 1	2X1mm ²		
Terminal Capacity 2	2x1.5mm ²		
Earth Terminal Capacity 1	5x1mm ²		
Earth Terminal Capacity 2	4X1.5mm ²		
Earth Terminal Capacity 3	3X2.5mm ²		
Earth Terminal Capacity 4	1X4mm² Multi-Strand		
Earth Terminal Capacity 5	1X6mm ²		
Product Class 1	Face plate muct be earthed		
Ambient Operating Temperature	-5°C to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
Additional Notes	Trailing Edge & Leading Edge Dimmer		

741XLEDITB100 - Hartland Satin Steel 1g 100W LED 2 Way Push On/Off Rotary Dimmer Satin Steel

WEB

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

741XLEDITB100

Hartland | HARTLAND RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers

All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Ilustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 18 August 2021 08:07 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84		COMERCIA ADDOCT

WEB