


Code: 7445VW

## Hartland | HARTLAND RANGE | Double Pole Switches

### Product Image



### Wiring




### Dimensions

**Hamilton®**  
HARTLAND

45V

Double Pole Red Rocker & Neon Vertical Mounted



### Insert Type

1 gang 45A Double Pole Red Rocker + Neon (Vertically Mounted)

### Insert Colour

Red/White

### EAN13 Barcode

5017503244997

### Commodity Code

85363030

### Luckins TSI

385552655

### Dimensions(Nominal)

Double: Height = 144.5mm Width = 88.0mm Depth = 5.0mm

### Weight

200 GR

### Switched Poles

Double

### Current Rating

45 Amp

### Voltage

220/250V AC

### Maximum Load

45 Amp

### Mains Frequency

50Hz

### IP Rating

IP2XD

### Contact Gap Minimum

3mm

### Terminal Capacity 1

3x6mm<sup>2</sup>

### Terminal Capacity 2

2x10mm<sup>2</sup>

### Terminal Capacity 3

1x16mm<sup>2</sup>

### Earth Terminal Capacity 1

3x6mm<sup>2</sup>

### Earth Terminal Capacity 2

2x10mm<sup>2</sup>

### Earth Terminal Capacity 3

1 x 16mm<sup>2</sup>

### Product Class 1

Must be earthed

### Ambient Operating Temperature

-5° to +40°C

### Recommended Location

Internal Use Only

### Maximum Installation Altitude

2000m

### Standard/Approval

BS EN 60669-1

### Additional Notes

Must be mounted vertically

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,  
4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: [info@hamilton-litestat.com](mailto:info@hamilton-litestat.com) | W: [www.hamilton-litestat.com](http://www.hamilton-litestat.com)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 2/28/2023 4:44:38 PM E&OE