

# making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

### 73TPWH-W

## Hartland | HARTLAND RANGE | Rocker Switches

Primary Range Hartland Insert Type 1 gang 10A Triple Pole Rocker Insert Colour White/White EAN13 Barcode 501750320501 Commodity Code 85363010 Luckins TSI 385552435 Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 111 GR Switched Poles Triple Current Rating 10A Voltage 220/250V AC Maximum Load 10 Amp resistive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 5mm Terminal Capacity 1 Sxlmm² Terminal Capacity 1 Sxlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 5 1x6.5mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 5 1x6.5mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 3 1x6.5mm² Earth Terminal Capacity 4 1x4.5mm² Earth Terminal Capacity 5 1x6.5mm² Earth Terminal Capacity 4 1x4.5mm² Earth Terminal Capacity 4 1x4.5mm² Earth Terminal Capacity 5 1x6.5mm² Earth Terminal Capacity 4 1x4.5mm² Earth Terminal Capacity 5 1x6.5mm² Earth Terminal Capacity 4 1x4.5mm² Earth Terminal Capacity 5 1x6.5mm² Earth Terminal Capacity 6 1x6.5mm² Earth Terminal Capacity 7 1x6.5mm² Earth Terminal Capacity 8 1x6.5mm² E	Item Image	Wiring	Dimensions	
Insert Type			HARTLAND TP Triple Pole Rocker	
Insert Type I gang 10A Triple Pole Rocker Insert Colour White/White EAN13 Barcode 5017503230501 Commodity Code 85363010 Luckins TSI 385552435 Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 111 GR Switched Poles Triple Current Rating 10A Voltage 220/250V AC Maximum Load 10 Amp resistive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 5mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 4 1x6mm² Earth Terminal Capacity 5 5x1mm² Earth Terminal Capacity 4 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x4mm² Multi-strand Earth Terminal Capacity 9 1x6mm² Ear	Primary Range	Hartland		
Insert Colour White/White EAN13 Barcode 5017503230501 Commodity Code 85363010 Luckins TSI 385552435 Dimensions(Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm Weight 111 GR Switched Poles Triple Current Rating 10A Voltage 220/250V AC Maximum Load 10 Amp resistive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Earth Terminal Capacity 6 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	<u> </u>			
Commodity Code         85363010           Luckins TSI         385552435           Dimensions(Nominal)         Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm           Weight         111 CR           Switched Poles         Triple           Current Rating         10A           Voltage         220/250V AC           Maximum Load         10 Amp resistive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5 xlmm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         1x2.5mm²           Terminal Capacity 4         1x4mm² Multi-strand           Terminal Capacity 5         1x6mm²           Earth Terminal Capacity 2         4x1.5mm²           Earth Terminal Capacity 3         3x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           Earth Terminal Capa		· ·		
Luckins TSI         385552435           Dimensions(Nominal)         Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm           Weight         111 GR           Switched Poles         Triple           Current Rating         10A           Voltage         220/250V AC           Maximum Load         10 Amp resistive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         5x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         1x2.5mm²           Terminal Capacity 4         1x4mm² Multi-strand           Terminal Capacity 5         1x6mm²           Earth Terminal Capacity 1         5x1mm²           Earth Terminal Capacity 3         3x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           Earth Terminal Capacity 5         1x6m²           Forduct Class	EAN13 Barcode			
Dimensions(Nominal)  Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm  Weight  111 GR  Switched Poles  Triple  Current Rating  10A  Voltage  220/250V AC  Maximum Load  10 Amp resistive  Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  5 xlmm²  Terminal Capacity 2  4xl.5mm²  Terminal Capacity 3  1x2.5mm²  Terminal Capacity 4  1x4mm² Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  5xlmm²  Earth Terminal Capacity 1  5xlmm²  Earth Terminal Capacity 4  1x4mm² Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  4xl.5mm²  Earth Terminal Capacity 3  3x2.5mm²  Earth Terminal Capacity 4  1x4mm² Multi-strand  Earth Terminal Capacity 3  3x2.5mm²  Earth Terminal Capacity 4  1x4mm² Multi-strand  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Foduct Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only	Commodity Code	85363010		
Weight 111 GR Switched Poles Triple Current Rating 10A Voltage 220/250V AC Maximum Load 10 Amp resistive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 2 4xl.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Luckins TSI	385552435		
Switched Poles Triple Current Rating 10A Voltage 220/250V AC Maximum Load 10 Amp resistive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5xlmm² Terminal Capacity 2 4xl.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5xlmm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x4mm² Multi-strand Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 9 1x4mm² Multi-strand Earth Terminal Capacity 9 1x4mm² Multi-strand Earth Terminal Capacity 9 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only	Dimensions(Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm		
Current Rating 10A  Voltage 220/250V AC  Maximum Load 10 Amp resistive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 xlmm²  Terminal Capacity 2 4x1.5mm²  Terminal Capacity 3 1x2.5mm²  Terminal Capacity 4 1x4mm² Multi-strand  Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 1 5xlmm²  Earth Terminal Capacity 3 1x2.5mm²  Earth Terminal Capacity 4 1x4mm² Multi-strand  Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 1 5xlmm²  Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	Weight	111 GR		
Voltage 220/250V AC  Maximum Load 10 Amp resistive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 x1mm²  Terminal Capacity 2 4x1.5mm²  Terminal Capacity 3 1x2.5mm²  Terminal Capacity 4 1x4mm² Multi-strand  Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 3 3 x2.5mm²  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	Switched Poles	Triple		
Maximum Load 10 Amp resistive  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 xlmm²  Terminal Capacity 2 4xl.5mm²  Terminal Capacity 3 1x2.5mm²  Terminal Capacity 4 1x4mm² Multi-strand  Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 1 5xlmm²  Earth Terminal Capacity 2 4xl.5mm²  Earth Terminal Capacity 3 1x2.5mm²  Earth Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 1 5xlmm²  Earth Terminal Capacity 2 4xl.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	Current Rating			
Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 5 x1mm²  Terminal Capacity 2 4x1.5mm²  Terminal Capacity 3 1x2.5mm²  Terminal Capacity 4 1x4mm² Multi-strand  Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 3 1x4mm² Multi-strand  Earth Terminal Capacity 3 1x4mm² Multi-strand  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	Voltage	220/250V AC		
IP RatingIP2XDContact Gap Minimum3mmTerminal Capacity 15 xlmm²Terminal Capacity 24xl.5mm²Terminal Capacity 31x2.5mm²Terminal Capacity 41x4mm² Multi-strandTerminal Capacity 51x6mm²Earth Terminal Capacity 15x1mm²Earth Terminal Capacity 24x1.5mm²Earth Terminal Capacity 33 x2.5mm²Earth Terminal Capacity 41x4mm² Multi-strandEarth Terminal Capacity 51x6mm²Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use Only	Maximum Load	10 Amp resistive		
Contact Gap Minimum  Terminal Capacity 1  5 x1mm²  Terminal Capacity 2  4x1.5mm²  Terminal Capacity 3  1x2.5mm²  Terminal Capacity 4  1x4mm² Multi-strand  Terminal Capacity 5  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Ix4mm² Multi-strand  Earth Terminal Capacity 5  Ix6mm²  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only	Mains Frequency			
Terminal Capacity 1 5 x1mm²  Terminal Capacity 2 4x1.5mm²  Terminal Capacity 3 1x2.5mm²  Terminal Capacity 4 1x4mm² Multi-strand  Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 3 3 x2.5mm²  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only				
Terminal Capacity 2 4x1.5mm²  Terminal Capacity 3 1x2.5mm²  Terminal Capacity 4 1x4mm² Multi-strand  Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 3 3x2.5mm²  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only				
Terminal Capacity 3  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 1  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Terminal Capacity 4  Terminal Capacity 5  Terminal Capacity 5  Terminal Capacity 6  Terminal Capacity 6  Terminal Capacity 7  Terminal Capacity 8  Terminal Capacity 9  Termin				
Terminal Capacity 4   1x4mm² Multi-strand   Terminal Capacity 5   1x6mm²   Sx1mm²   Sx1mm²   Sx1mm²   Sx1mm²   Sx1mm²   Sx1mm²   Sx1mm²   Sx1mm²   Sx2.5mm²   Sx2.5mm²   Sx2.5mm²   Sx1mm²   Sx1mm²   Sx1mm²   Sx1mm²   Sx2.5mm²   Sx2.5mm²   Sx2.5mm²   Sx2.5mm²   Sx2.5mm²   Sx2.5mm²   Sx2.5mm²   Sx3.5mm²   Sx3.				
Terminal Capacity 5   1x6mm²				
Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 3 3 x2.5mm²  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only				
Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 3 3 x2.5mm²  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	-			
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Ix4mm² Multi-strand  Earth Terminal Capacity 5  Ix6mm²  Product Class 1  Ambient Operating Temperature  Recommended Location  Antient Operation Internal Use Only				
Earth Terminal Capacity 4   1x4mm² Multi-strand   Earth Terminal Capacity 5   1x6mm²   Product Class 1   Must be earthed   Ambient Operating Temperature   -5° to +40°C   Recommended Location   Internal Use Only				
Earth Terminal Capacity 5   1x6mm²   Product Class 1   Must be earthed   Ambient Operating Temperature   -5° to +40°C   Recommended Location   Internal Use Only	•			
Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only	•			
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only				
Recommended Location Internal Use Only				
·				
Maximum Installation Altitude 2000m	Maximum Installation Altitude	2000m		

73TPWH-W - Hartland Bright Steel 1 gang 10A Triple Pole Rocker White/White



making connections beautifully

#### Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

#### 73TPWH-W Hartland | HARTLAND RANGE | Rocker Switches Standard/Approval BS EN 60669-1 It is the policy of the company to All products listed conform to current All accessories are manufactured improve products as part of our British or European standard and the under an accredited BS EN ISO 9001: development programme. Therefore, product information is correct at the 2015 Quality Management System. we reserve the right to alter designs time of going to press. and dimensions without prior notice. Illustrations and diagrams are Due to manufacturing processes we reproduced within the limitations of cannot guarantee an exact colour Correct as at 18 August 2021 08:05 AM reproduction and printing process and match and shadings of of certain E&OE are not binding. finishes. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84