DATASHEET



Code: 7G24TCSQG

Hartland G2 | HARTLAND G2 RANGE | Telephone and Data Outlets

Product Image



Wiring

Pin No.	BT Wiring Schedule Colour Codes: Striped Wires
\Box	GREEN / White
121	BLUE / White
1 3 1	ORANGE / White
4	WHITE / Orange
5	WHITE / Blue
6	WHITE / Green
Ma	ain Wire Colour shown in CAPITALS

Incoming Telephone Cable
On 4 wire systems, Pin 1 and 6
are not connected.

The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1; Pin 2 to Pin 2; etc. as shown in the diagram above.

Dimensions



Insert Type	1 gang Telephone Slave
Insert Colour	Quartz Grey
EAN13 Barcode	5051164002848
Commodity Code	85176990
Luckins TSI	407518551
Dimensions(Nominal)	Single: Height = 87.4mm Width = 87.4mm Depth = 4.65mm
Fixing Hole Centres	Box Fixing = 60.3mm
Switched Poles	N/A
Current Rating	n/a
IP Rating	IP2XD
Contact Gap Minimum	N/A
Earth Terminal Capacity 1	5x1mm²
Earth Terminal Capacity 2	4 x 1.5mm2
Earth Terminal Capacity 3	3 x 2.5mm2
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand
Earth Terminal Capacity 5	1 x 6mm2
Product Class 1	Must be earthed (refBS7671 415.2.1)
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only
Maximum Installation Altitude	2000m
Standard/Approval	BS 6312:2:2

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre,

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com