DATASHEET

making connections beautifully

Hamilton


Code: 74SS1USBSS-W Hartland | HARTLAND RANGE | USB Power Sockets

Product Image




Wiring

Wiring 13Amp Switched Single Sockets with USB Charging Outlet Meutral ZZZ Earth _____ Live



Dimensions



| Insert Type | 1 gang 13A Single Pole Switched Socket with 1 USB Outlet 1x2.1A |
|----------------------------------|--|
| Insert Colour | Satin Steel/White |
| EAN13 Barcode | 5017504088989 |
| Commodity Code | 85363010 |
| Luckins TSI | 404387552 |
| Dimensions(Nominal) | Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = N/A |
| Switched Poles | Single |
| Current Rating | 13 Amp, USB 1 x 2.1A |
| Voltage | 180/250V AC, USB = 5V |
| Maximum Load | 13 Amp, USB = 2.1A |
| Mains Frequency | 50/60Hz |
| IP Rating | IP2XD |
| Contact Gap Minimum | 3mm |
| Terminal Capacity 1 | 3x2.5mm² |
| Terminal Capacity 2 | 3x4mm² |
| Terminal Capacity 3 | 2x6mm ² Multi-Strand |
| Earth Terminal Capacity 1 | 3x2.5mm ² |
| Earth Terminal Capacity 2 | 3x4mm² |
| Earth Terminal Capacity 3 | 2x6mm ² Multi-Strand |
| Product Class 1 | Must be earthed |
| Ambient Operating Temperature | -15°C to +40°C |
| Recommended Location | Internal Use Only |
| Maximum Installation Altitude | 2000m |
| Standard/Approval | BS1363 BS EN 62368 |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | W: www.hamilton-litestat.com

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was generated on 5/17/2023 12:13:57 PM E&OE