

# JC030067

## Commercial Linear

Commercial Linear 5FT 30W/32W/34W/36W 4000K Microwave On/Off

### Features & Benefits

- Four Wattage output selectable allowing you to choose between 22W, 25W, 28W and 31W
- DALI/Switch dimmable and Microwave on/off options
- 4ft(1200mm) or 5ft(1500mm) options
- 4000K Colour temperature as standard
- Self-test emergency as standard
- Anti- tamper end caps
- Up to 156 LpcW
- This product contains a light source of energy efficiency class C



### General Information

Mounting	Surface Mount
Environment	Indoor
Suitable For Zones	Outside Zone 2
Product Group	Surface Linear
Color Finish	White
Product Range	Commercial Linear
Overall Dimensions	1500 x 164 x 48mm
Length (mm)	1500
Width (mm)	164
Height (mm)	48
Product Weight(kg)	2.840
Light Source	LED
Method of fix	Screw fix or suspend
IP Rating	IP20
Origin of manufacturer	Made in China
Warranty	5 Year Warranty (See Website for terms and conditions)
Mounting height	2.5-6m
Driver manufacturer	AGT
LED manufacturer/type	Jufei/2835

Customs Tariff code\*\*

9405119090

Electrical

Voltage Rating	220-240V~
Primary Running Current(Amp)	0.07-0.26
Inrush current(Amps)	18
Operating Frequency Hz	50/60Hz
Secondary running current(mA)	260/280/300/320
Constant Current or Constant Voltage	CC
Luminaire Circuit Wattage1	30
Luminaire Circuit Wattage2	32
Luminaire Circuit Wattage3	34
Luminaire Circuit Wattage4	36
Class	I
Output Voltage Max/Range (VDC)	60-125
Total Harmonic Distortion (THD)%	15
EMC Compliant (EN55015)	Yes
Power Factor Correction	0.95
Input Electrical Connections	Live, Earth Neutral
Dimmable	No

Thermals

Thermal Cut Out	Yes
Operating Temperature Range °C	0-60

Performance Data

LED Life (Hours)*	60000
Energy Rating	This product contains a light source of energy efficiency class C
Actual Lumen Output1	4550
Actual Lumen Output2	4870
Actual Lumen Output3	5200
Actual Lumen Output4	5260
Lumens Per Circuit Watt1	152
Lumens Per Circuit Watt2	152
Lumens Per Circuit Watt3	153
Lumens Per Circuit Watt4	156
Standard Deviation Colour Matching - SDCM	3
Color Rendering Index	80-89
CRI: Ra	87
Correlated Colour Temperature1	4000K
Beam Angle °	112
LOR (Light Output Ratio) %	100
Photometry Available	Yes

Controls and Sensors

Detection Distance	6m
Detection Motion Speed	0.5m/sec
Installation Height	2.5-6m
Detection area	100% / 75% / 50% / 25%
Detection angle	Ceiling mount 150°
Hold time	5S/30S/60S/3min/5min/10min/20min/30min
Microwave frequency	5.8 GHz ±74.9 MHz.ISM wave band
Daylight Sensor (On/Off) (NOT Daylight Harvesting)	2Lux/10Lux/25Lux/50Lux/Disable

Construction

Primary Material	Pressed Steel
Outer Diffuser	PMMA
LED Brand	Jufei
Lens	Polycarbonate
Driver Housing	Metal



Packaging

Product carton overall dimensions(cm)	157.3 x 17 x 5.2cm
Product Packaged Weight(kg)	3.2
Quantity Per Outer Carton	6
Outer carton(L)- cm	159.7
Outer carton(W)- cm	36.8
Outer carton(H)- cm	19.7
Outer carton Net weight- kg	19.2
Outer carton Gross weight- kg	20.47
Product Bar Code EAN-13 Number	5052544119767
Outer carton Bar Code ITF-14 Number	15052544119764

Standards & Approvals

Manufactured in accordance to	BS EN 60598-2-1
CE Marked	Yes
UKCA Marked	Yes
Date code/Purchase order No.	Yes
WEEE symbol	Yes
Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001-2015, ISO14001-2015





\*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

\*\*JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT.  
Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | [sales@jcc.co.uk](mailto:sales@jcc.co.uk) | [www.jcc.co.uk](http://www.jcc.co.uk)  
Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 79 [26/03/2025]