

JC077087BLK


Line Of Light Emergency

Line of Light 1200mm 40W IP20 3000/4000/5700K DALI/Switch Dim
UGR Emergency Black

 Main Product Image

Features & Benefits

- Two-part construction allowing easy access to termination and internal components
- Available in 4ft and 5ft lengths
- Available in white, silver and black
- Colour selectable between 3000K, 4000K & 5700K
- Illuminated corners & upward illumination options
- Suspension kit available
- Linking kit (JC077156) available to assemble longer lengths, squares and rectangle configurations
- Sections and corners can be connected via a simple plug and play system
- For longer seamless runs add /EXT to any standard Line of Light product codes to order middle/end pieces that exclude end caps and flex



General Information

Mounting	Surface or Suspended
Suitable For Zones	Outside Zone 2
Product Group	Commercial Linear
Color Finish	Black
Product Shape	Rectangular
Product Range	Line Of Light
Overall Dimensions	1205 x 60 x 78
Length (mm)	1205
Width (mm)	60
Height (mm)	78
Light Source	LED
Light Source Features	3CCT Selectable

Additional Information

Luminaire Accessories

Fixing centres

IP Rating

Origin of manufacturer

Warranty

Dimming Protocol Compatibility

Driver manufacturer

LED manufacturer/type

Electrical

Voltage Rating

Primary Running Current(Amp)

Inrush current(Amps)

Operating Frequency Hz

Secondary running current(mA)

Constant Current or Constant Voltage

Luminaire Circuit Wattage1

Class

Output Voltage Max/Range (VDC)

Total Harmonic Distortion (THD)%

EMC Compliant (EN55015)

Power Factor Correction

Input Electrical Connections

Dimmable

Emergency Data

Load Voltage(DC)

LOR % in Emergency Mode

Minimum Battery run time

Recharge Time

Inverter PFC

Battery Data

Battery Specification

Battery Type

Nominal battery current

Charge Current

Recharge Time

Deep Discharge Protection

It is advised not to mix 1205mm and 1505mm fittings on the same connected layout- surface diffuser brightness may vary between the different lengths

JC077156 linking kit, JC077150 Corner(add BLK/SIL/WH), JC077153 2m suspension kit(add BLK/SIL/WH), JC077154 5m suspension kit(add BLK/SIL/WH)

See instruction hseet

20

China

5 Year Warranty inc batteries(Terms & conditions apply)

DALI/Sw dim

BOKE

Shaanxi/2835

220-240

0.3

4.75A peak ,162us duration(50 % Ipeak)

50/60Hz

550-1300

CC

40

I

6-42

10

Yes

0.95

Live, Earth, Neutral

DALI-2(DT-6)/Switch dim

20-50

5

3 hours

24 hours

0.5

3.2V 3300mAh

LifePO4

3.3A

0-250mA

24 hours

Yes

Thermals

Thermal Cut Outyes

Performance Data

LED Life (Hours)*	50000
Energy Rating	This product contains a light source of energy efficiency class E
Actual Lumen Output1	4200
Lumens Per Circuit Watt1	105
Color Rendering Index	80-89
CRI: Ra	80
Correlated Colour Temperature1	3000
Correlated Colour Temperature2	4000
Correlated Colour Temperature3	5700
Beam Angle °	70
LOR (Light Output Ratio) %	100
Photometry Available	Yes


Construction

Primary Material	Aluminium
Outer Diffuser	Polycarbonate
Driver Housing	Polycarbonate

Standards & Approvals

Manufactured in accordance to	BS EN 60598-2-1,2-22
CE Marked	Yes
UKCA Marked	Yes
Date code/Purchase order No.	Yes
WEEE symbol	Yes
Certificate Of Conformity	Available on request
Accredited Members	LIA, ISO9001-2015, ISO14001-2015





*Hours life stated is an indication of expected L70 chip and light output calculations when operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT.
Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk
Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 70 [26/03/2025]