

JCEM003

## Pro Batten Range Internal Emergency packs

Pro Batten Range Internal Emergency pack IP20



### Features & Benefits

- Standard and Self-test Emergency pack options for use with ToughLED™ Pro and Skypack™ Pro Range
- Plug and play connectors for simple conversion of the Pro Batten range to emergency fittings
- LifePO4 Lithium batteries
- 5 year extended Warranty
- 



### General Information

Mounting	<b>Integrated into gear tray</b>
Trade Name	<b>ToughLED™ Pro</b>
Product Group	<b>Weatherproof Battens</b>
Color Finish	<b>Green</b>
Product Shape	<b>Rectangular</b>
Product Range	<b>ToughLED™ Pro</b>
Length (mm)	<b>234.2</b>
Width (mm)	<b>49.2</b>
Height (mm)	<b>36.7</b>
Product Weight(kg)	<b>0.35</b>
IP Rating	<b>IP20</b>
Origin of manufacturer	<b>Made in China</b>
Warranty	<b>5 Year Warranty (5 years on batteries)(See Website for terms and conditions)</b>
Operation Type	<b>Maintained only</b>
Customs Tariff code**	<b>8536303099</b>

### Electrical

Voltage Rating **220-240**

Primary Running Current(Amp)	<b>0.05</b>
Inrush current(Amps)	<b>7</b>
Operating Frequency Hz	<b>50/60Hz</b>
Secondary running current(mA)	<b>220-25</b>
Luminaire Circuit Wattage1	<b>2W max Output</b>
Power Factor Correction	<b>0.5</b>
Input Electrical Connections	<b>Plug and Play connectors</b>

## Emergency Data

Load Voltage(DC)	<b>9-75</b>
LOR % in Emergency Mode	<b>Please refer to ToughLED™ Pro Emergency fittings datasheets</b>
Minimum Battery run time	<b>3</b>
Recharge Time	<b>24hrs</b>

## Battery Data

Battery Specification	<b>LiFePO4 6.4V</b>
Battery Type	<b>Lithium Iron</b>
Nominal battery current	<b>1.8Amp</b>
Charge Current	<b>250mA</b>
Recharge Time	<b>24hrs</b>
Battery Total Weight(kg)	<b>0.084</b>

## Thermals

Operating Temperature Range °C	<b>0 to +50</b>
--------------------------------	-----------------

## Construction

Primary Material	<b>Polycarbonate</b>
------------------	----------------------

## Packaging

Product Packaged Weight(kg)	<b>0.39</b>
Quantity Per Outer Carton	<b>30</b>
Outer carton(L)- cm	<b>43.5</b>
Outer carton(W)- cm	<b>27.5</b>
Outer carton(H)- cm	<b>21.5</b>
Outer carton Net weight- kg	<b>11.7</b>
Outer carton Gross weight- kg	<b>12.2</b>
Product Bar Code EAN-13 Number	<b>5052544110832</b>
Outer carton Bar Code ITF-14 Number	<b>15052544110839</b>

## Standards & Approvals

Manufactured in accordance to	<b>BS EN 60598:2015, 2-22</b>
CE Marked	<b>Yes</b>

UKCA Marked	<b>Yes</b>
Date code/Purchase order No.	<b>Yes</b>
WEEE symbol	<b>Yes</b>
Certificate Of Conformity	<b>Available on request</b>
Accredited Members	<b>LIA, ISO9001-2015, ISO14001-2015</b>

\*\*JCC Lighting Limited makes every effort to ensure that the Customs Tariff information in this document is timely and accurate. However, it's not possible for us to assure the absolute veracity and completeness of that information, as errors may occur. The placement of any inaccurate tariff information is completely unintentional. JCC Lighting Limited reserves the right, in its sole discretion, to correct any errors or omissions to the tariff code and to make any and all changes contained in this document at any time and without notice. It is the sole responsibility of the importer to ensure that the commodity code advised is correct for the products/goods being supplied by JCC Lighting Limited. JCC Lighting Limited does not assume any liabilities, losses, costs, and expenses arising out of or related to the importers use of this commodity code or the information related to the import of any JCC Lighting products.

---

JCC Lighting LTD, Lux Park, Chichester Business Park, City Fields Way, Tangmere, Chichester, West Sussex, PO20 2FT.  
Sales: 01243 838999 (8am to 5pm Monday to Friday) Fax: 01243 838998 | [sales@jcc.co.uk](mailto:sales@jcc.co.uk) | [www.jcc.co.uk](http://www.jcc.co.uk)  
Company Registration Number: 03044848 | VAT Number: 918544112

This document is uncontrolled if printed, all information is subject to change

Version 131 [26/03/2025]