

4 4 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Nitro



06453 NTR03/COR

Nitro corridor optics, 3W EME downlight, non-maintained

- Standard and corridor version with different lens
- Non-maintained, >3hrs



Overview

The Nitro LED Non-Maintained Emergency Downlights are discrete recessed fittings that provide emergency lighting only. Options of a standard lens design with a circular light pattern or a corridor version lens with a beam that is designed to emphasis illumination along one axis more than the other. Self-test version available.



IP20



General Information

IP Rating	IP20
Protection Rating	Class II
Installation Area	Internal
UEM/EME Protection	Class II

Technical Summary	
Product Code	NTR03/COR
Maximum Efficiency	154 lm/W
Emergency Luminous Flux	150 lm
Maintained Luminous Flux	200 lm
Weight	0.10Kg
Dimensions (L x W x D) (mm)	33xØ70
Cut-Out (mm)	Ø50mm
UEM/EME Battery Life	4 y
UEM/EME Input Voltage	220-240Vac 50/60Hz
UEM/EME Ambient Temperature Range	0°C to 45°C
UEM/EME Power Factor	0.4
Emergency Modes	Non-maintained Only
UEM/EME Test Function	Manual
UEM/EME CCT	6,000 K
UEM/EME Input Power (Max)	3 W
UEM/EME Protection	Class II
UEM/EME Dimensions (L x W x D) (mm)	28 x 70 Ø (mounting recessed 50mm cut-out)
UEM/EME Emergency Operation Test	Manual



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

4 4 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Nitro



06453 NTR03/COR

Accessories

Product Code	Description	Type
KBAT2000LI1	Li-ion battery 3.7V 2000mAh for self test DD EME	Battery

Overview

The Nitro LED Non-Maintained Emergency Downlights are discrete recessed fittings that provide emergency lighting only. Options of a standard lens design with a circular light pattern or a corridor version lens with a beam that is designed to emphasis illumination along one axis more than the other. Self-test version available.




IP20




General Information




IP Rating	IP20
Protection Rating	Class II
Installation Area	Internal
UEM/EME Protection	Class II



NTR03



NTR03/COR



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com