



SKT SW INT 16A 3P 110V IP44 4H MOULDED

SURFACE SWITCH INTERLOCK 2P+E 16A 110V 4H IP44



PM16/3300NFPB

Switched socket with mechanical interlock

TECHNICAL DATA		REGISTRY	
Rated current	16A	Net weight	0.74KG
Frequency	50/60Hz	Gross Weight	0.88KG
Poles	2P+ 	EAN Code	8014950038244
Dimensions	260X108X135MM (HWD)	Min order quantity	1
Clock Position	4h	Dimensions	260X108X135MM (HWD)
Storage room temperature MAX	+70 °C		
IP Protection degree	IP44		
Rated operating voltage	110V		
Manufacturing material	Technopolymer Recyclable Palazzoli		
		REFERENCE STANDARDS	STANDARDS
		EN 60309-1:1999	2014/35/EU (LVD)
		EN IEC 63000:2018	2011/65/EU (RoHS)
		EN 60309-1:1999/A2:2012	2012/19/EU (WEEE)
		EN 60309-2:1999	
		EN 60309-2:1999/A2:2012	
		EN 60309-1:1999/A1:2007	
		EN 60309-1:1999/A1AC:2014	
		EN 60309-2:1999/A1:2007	
		EN 60309-4:2007/A1:2012	
		EN 60309-4:2007	