

Technical Data Sheet

	roominati Bata Onoot				
Product number	6603AB	6603AB		Technical 2D/3D Line Drawing with Measurements	
Date:	30/06/2023	30/06/2023			
Product range					
Product name	Samson 3Lt Round Spotlight - Antique Brass, IP44				
Application	-	-			
Barcode	5053423096759	5053423096759			
Draduct Dataila	1	Daga Dataila			

Product Details Base Details Primary natural Scientess Steel and Mild Steel and Steel Stee	Barcode		5053423096759			
Secondary material I. Light details Colour Ancique Brass Primary lamp holder OU10 Finish 100 Primary lamp holder QU10 LED Total height (mm) 100 Primary lamp holder QU10 LED Height (mm) 100 Primary lamp holder QU10 LED Width (mm) 280 Secondary lamp holder number of lamps - Length (mm) 280 Secondary lamp holder number of lamps - Length (mm) 280 Secondary lamp holder number of lamps - Length (mm) 280 Secondary lamp holder number of lamps - Length (mm) 280 Secondary lamp holder number of lamps - Shade/glass/diffuser rinsh - Class - Shade/glass/diffuser material Stanlegas Steplic Glass Lumen output - Cut out (mm) I. Chisa Lumen output Cut out (mm) I. Chisa Lumen output Pire rated (Debutil) Electrical details Lumen output Bashroom xones	Product Details			Base Details		
Colour Anique Briss Primary Iamp holder GUI0 Finish - Primary Iamp holder number of lamps 3 Finish - Primary Iamp holder number of lamps 3 Total helgisk (mm) 160 Primary Iamp included No Width (mm) 200 Secondary Iamp holder - Length (mm) 200 Secondary Iamp holder number of lamps - Projection (mm) Image: Projection (mm) Secondary Iamp holder number of lamps - Shade/glass/diffuser colour Antique Brass and Frosted Glass Secondary Iamp included - Shade/glass/diffuser style 2 Closur temperature (K) - Cut out (mm) Electrical details - Fire rated (Conduit) Electrical details Fire rated (Conduit) Electrical details Fire rated (Conduit) Electrical details Fire rated (Conduit) Primary Iamp wattage 5 Bathroom zones 2 Operating voltage 220-2400 5000412 Height adjustable	Primary material	Stainless Ste	el and Mild Steel and Glass	Base dimensions (mm)		
Finish	Secondary material	-		Light details		
Total height (mm) 1600 Primary lamp type GUI LED Height (mm) 1600 Primary lamp included No Width (mm) 280 Secondary lamp holder - Length (mm) 280 Secondary lamp holder number of lamps - Projection (mm) Antique Brass and Frostod Glass Secondary lamp included - Shade/glass/diffuser finish - Class 2 (Double Insulatori) Shade/glass/diffuser material Stainless Stoel/Glass Lumen output - Shade/glass/diffuser style - Colour temperature (K) - Recess depth (mm) - CRI Fire rated (Default) Electrical details Be Training and Style - Secondary lamp wattage 20 2440 50/60/60/60 </td <td>Colour</td> <td>Antique Brass</td> <td>3</td> <td>Primary lamp holder</td> <td>GU10</td>	Colour	Antique Brass	3	Primary lamp holder	GU10	
Height (mm) 160 Primary lamp included No Width (mm) 280 Secondary lamp holder - Length (mm) 280 Secondary lamp holder mubber of lamps - Projection (mm) Antique Brass and Frostad Glass Secondary lamp tincluded - Shadefglass/diffuser colour Antique Brass and Frostad Glass Secondary lamp included - Shadefglass/diffuser style - Class 2 (Double Insulated) Shadefglass/diffuser style - Colour temperature (K) - Shadefglass/diffuser style - Colour temperature (K) - Shadefglass/diffuser style - Colour temperature (K) - Wide Cut (mm) - CRI - Cut out (mm) Beam (ageres) - - File rated (Default) Electrical details - P rating 44 Primary lamp watage 5 Bathroom cones - Perature (ageres) 2-2-2-2-0/5-50-60-bt Height adjustable details No Transformeridiver details <t< td=""><td>Finish</td><td colspan="2">-</td><td>Primary lamp holder number of lamps</td><td>3</td></t<>	Finish	-		Primary lamp holder number of lamps	3	
Note March	Total height (mm)	160		Primary lamp type	GU10 LED	
Length (mm) 200 Secondary lamp holder number of lamps ————————————————————————————————————	Height (mm)	160		Primary lamp included	No	
Projection (mm) Recondary lamp type - Shade/glass/diffuser colour Antique Brass and Frosted Glass Secondary lamp included - Shade/glass/diffuser material Stainless Steel/Glass Lumen output - Shade/glass/diffuser style Colour temperature (K) - Cut out (mm) CRI - Recess depth (mm) Image: Recess depth (mm) Electrical details Prating 44 Primary lamp watage 5 Bathroom Zones - Secondary lamp watage 220-240V 50/60/12 Bathroom Zones - Primary lamp watage 220-240V 50/60/12 Bathroom Zones No Dimmand provider details - Max drop for ceiling fittings (mm) No Dimmand provider details - Benery Lass NA	Width (mm)	280		Secondary lamp holder	-	
Shade/glass/diffuser colour Antique Brass and Frosted Glass Secondary lamp included	Length (mm)	280		Secondary lamp holder number of lamps		
Shade/glass/diffuser finish . Class 2 (Double Insulated) Shade/glass/diffuser style . Colour temperature (K) . Cut out (mm) . CRI . Recess depth (mm) . Beam angle (degrees) . Fire rated (Default) Electrical details . IP rating 44 Primary lamp wattage 5 Bathroom zones . Secondary lamp wattage 5 Height adjustable No Transformer/driver details . Height adjustable (adjustable) No Transformer/driver details . Adjustable details No Dimming method . Max drop for ceiling fittings (mm) Switch of . Minimum drop for ceiling fittings (mm) Switch location . Minimum drop for ceiling fittings (mm) All Indoor Lighting – 1 Year Guarantee . Efficacy (Indiv) All Indoor Lighting – 1 Year Guarantee . . Efficacy (Indiv) Supply cable lead teal length (mm) . . Ceiling cup ditails </td <td>Projection (mm)</td> <td></td> <td></td> <td>Secondary lamp type</td> <td>-</td>	Projection (mm)			Secondary lamp type	-	
Shade/glass/idffuser material Stainless Steel/Glass Lumen output Shade/glass/idffuser style - Colour temperature (K) - Cut out (mm) CRI CRI Recess depth (mm) Electrical details - Fire rated (Default) Electrical details - IP rating 44 Primary lamp wattage 5 Bathroom zones - Secondary lamp wattage 200-240V 50/60Hz Height adjustable No Transformer/driver details - Adjustable details No Dimmable - Adjustable details No Dimmable - Minimum drop for ceiling fittings (mm) Switch details - Minimum drop for ceiling fittings (mm) Switch location - Minimum drop for ceiling fittings (mm) Switch location - Berray class N/A Walranty details NA Efficacy (Im/w) Wall ack plate details NA Ceiling cup details Ceiling cup details NA Ceiling cup details <td>Shade/glass/diffuser colour</td> <td>Antique Brass</td> <td>s and Frosted Glass</td> <td>Secondary lamp included</td> <td>-</td>	Shade/glass/diffuser colour	Antique Brass	s and Frosted Glass	Secondary lamp included	-	
Shade/glass/diffuser style .	Shade/glass/diffuser finish	-		Class	2 (Double Insulated)	
Cut out (mm) CRI CRI Recess depth (mm) Beam angle (degrees) 1 Fire rated (Default) Electrical details IP rating 44 Primary lamp wattage 5 Bathroon zones - Secondary lamp wattage 20-240V 50/60Hz Tilt angle (degrees) - Operating voltage 220-240V 50/60Hz Helght adjustable No Transformer/driver details 220-240V 50/60Hz Max drop for ceiling fittings (mm) Dimmable - Minimum drop for ceiling fittings (mm) Switch ocal - Minimum drop for ceiling fittings (mm) Switch location - Smry class N/A Switch type - Befing cup class N/A Switch type N/A Warranty details All Indoor Lighting - 1 Year Guarantee Elling cup details N/A Ceiling cup J Back plate detat Supply cable total length (mm) Supply cable colour N/A Ceiling cup du diansions (mm) Supply cable length from base/lampholder (mm) Supply cable length from base/lampholder (mm) Supply cable length from base	Shade/glass/diffuser material	Stainless Ste	el/Glass	Lumen output		
Recess depth (mm) Beam angle (degrees) Image (Default) Electrical details IP rating 44 Primary lamp waitage 5 Bathroom zones - Secondary lamp waitage 20°-240V 50/60Hz Height adjustable No Operating voltage 22°-240V 50/60Hz Height adjustable No Transformer/driver details 22°-240V 50/60Hz Max drop for ceiling fittings (mm) Dimmable - Max drop for ceiling fittings (mm) Switched - Miniminum drop for ceiling fittings (mm) Mo Switched Miniminum drop for ceiling fittings (mm) Mo Switched Marranty details N/A Switch location - Befracy (m/w) Switch location - Ceiling cup / Back plate details Supply cable colour NA Supply cable longth (mm) Supply cable colour - Ceiling cup flash (pm) Supply cable longth from base/lampholder (nm) Supply cable longth from base/lampholder to switch (nm) Ceiling cup rixinh - Packaging details Ceiling cup fixing -	Shade/glass/diffuser style	-		Colour temperature (K)	-	
Fire rated (Default) Electrical details IP rating 44 Primary lamp wattage 5 Bathroom zones - Secondary lamp wattage 220-240V 50/60Hz Tilit angle (degrees) - Operating voltage 220-240V 50/60Hz Height adjustable No Transformer/driver details - Max drop for ceiling fittings (mm) Dimmable - Max drop for ceiling fittings (mm) Dimmable - Minimum drop for ceiling fittings (mm) Switch docation - Marranty details All Indoor Lighting – 1 Year Guarantee Switch location - Efficacy (im/w) All Indoor Lighting – 1 Year Guarantee Plug details NA Ceiling cup f Back plate details Supply cable total length (mm) NA Ceiling cup details Supply cable colour - Ceiling cup details Supply cable length from selling cup to lampholder (mm) Supply cable length from selling type to lampholder (mm) Ceiling cup fixing Supply cable length from switch to plug (mm) - Ceiling cup fixing Supply cable length (metres) 0.16	Cut out (mm)			CRI		
P rating	Recess depth (mm)			Beam angle (degrees)		
Bathroom zones . Secondary Immp waitage . Tilt angle (degrees) - Operating voltage 220-240V 50/60Hz Height adjustable No Transformer/driver details - Max drop for ceiling fittings (mm) Dimmable - Minimum drop for ceiling fittings (mm) Switched - Minimum drop for ceiling fittings (mm) Switch deatlin - Warranty details All Indoor Lighting – 1 Year Guarantee Switch type - Efficacy (Infw) Description of Lighting – 1 Year Guarantee Plug details NA Ceiling cup / Back plate details Supply cable total length (mm) - Ceiling cup dimensions (mm) Pupply cable colour - Ceiling cup details Supply cable length from base/lampholder (mm) Supply cable length from switch to plug (mm) Ceiling cup details Supply cable length from switch to plug (mm) - Ceiling cup finish Supply cable length from switch to plug (mm) - Ceiling cup fixing Unit box height (metres) 0.16 Ceiling cup fixing Unit box length (metres) 0.17	Fire rated	(Default)		Electrical details		
Tilt angle (degrees) - Operating voltage 220-240V 50/60Hz Height adjustable No Transformer/driver details - Adjustable details No Dimmable - Max drop for ceiling fittings (mm) Dimming method - Minimum drop for ceiling fittings (mm) Switched - Minimum drop for ceiling fittings (mm) Switched - Energy class N/A Switched - Warranty details All Indoor Lighting – 1 Year Guarantee Plug details NA Efficacy (Im/w) Switch type - Ceiling cup f Back plate details Supply cable total length (mm) NA Supply cable colour - - Ceiling cup details Supply cable total length (mm) - Ceiling cup details Supply cable length from base/lampholder to switch - Ceiling cup prinsh - Supply cable length from switch to plug (mm) - Ceiling cup finish - Packaging details - Ceiling cup fixing - Unit box length (metres) 0.16 <td>IP rating</td> <td>44</td> <td></td> <td>Primary lamp wattage</td> <td>5</td>	IP rating	44		Primary lamp wattage	5	
Height adjustable No Transformer/driver details	Bathroom zones	-		Secondary lamp wattage		
Adjustable details No Dinmable Dinming method Dinuin Dinu	Tilt angle (degrees)	-		Operating voltage	220-240V 50/60Hz	
Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Max drop for ceiling fittings (mm) Minimum drop for ceiling fittings (mm) Max drop for ceiling fittings (mm) Minimum drop for ceiling club for all length from fittings (mm) Minimum drop for ceiling club fit length from fittings (mm) Minimum drop for ceiling club fit length from fittings (mm) Minimum drop for ceiling club fit length from fittings (mm) Minimum drop for ceiling club fit length from fittings (mm) Minimum drop for ceiling club fit length from fittings (mm) Minimum drop for ceiling club fit length from fittings (mm) Minimum drop for ceiling club fit length from fittings (mm) Minimum drop for ceiling club from for fittings (mm) Minimum drop for ceiling club from for fittings (mm) Minimum drop for ceiling club from for fittings (mm) Minimum drop for ceiling club from for fittings (mm) Minimum drop for ceiling club from for fittings (mm) Minimum drop for ceiling club from for fittings (mm) Minimum drop for fitting (mm) Minimum drop for ceiling club from for fitting club from for fi	Height adjustable	No		Transformer/driver details		
Minimum drop for ceiling fittings (mm) Switch location Switch location Switch location Switch type Switch type Plug details NA Supply cable total length (mm) Supply cable colour Chain length from ceiling cup to lampholder (mm) Supply cable length from base/lampholder to switch (mm) Ceiling cup details Supply cable length from switch to plug (mm) Ceiling cup details Supply cable length from switch to plug (mm) Ceiling cup finish Supply cable length from switch to plug (mm) Ceiling cup finish Supply cable length from switch to plug (mm) Ceiling cup material Supply cable length from switch to plug (mm) Ceiling cup fixing Di30xH25 Unit box height (metres) O.17 Ceiling cup fixing Di30xH25 Unit box net weight (kg) O.75 Ceiling but height (metres) O.95 Ceiling cup finish Ceiling cup finish Ceiling cup fixing Ceilin	Adjustable details	No		Dimmable	-	
Common C	Max drop for ceiling fittings (mm)			Dimming method	-	
Marranty details MI Indoor Lighting - 1 Year Guarantee					-	
### All Indoor Lighting – 1 Year Guarantee Efficacy (Im/w) Ceiling cup / Back plate details Ceiling cup dimensions (mm) Ceiling cup details Ceiling cup base Ceiling cup details Ceiling cup shape - Chain length from ceiling cup to lampholder (mm) Supply cable length from base/lampholder to switch (mm) Supply cable length from base/lampholder to switch (mm) Ceiling cup colour Ceiling cup finish Ceiling cup finish Ceiling cup material Ceiling cup fixing - Unit box height (metres) Unit box length (metres) Unit box net weight (kg) Unit box poss weight (kg) All Indoor Lighting – 1 Year Guarantee Plug details NA Supply cable total length (mm) Chain length from ceiling cup to lampholder (mm) Supply cable length from base/lampholder to switch (mm) Supply cable length from base/lampholder to switch (mm) Supply cable length from base/lampholder to switch (mm) Supply cable length from base/lampholder to switch (mm) Supply cable length	, ,	N/A		Switch location	-	
Ceiling cup / Back plate details Ceiling cup dimensions (mm) Ceiling cup details Ceiling cup betails Ceiling cup details Ceiling cup shape Ceiling cup colour Ceiling cup finish Ceiling cup fixing C	Warranty details	All Indoor Lig	hting – 1 Year Guarantee	Switch type	-	
Ceiling cup / Back plate details Ceiling cup dimensions (mm) Ceiling cup details Ceiling cup shape Ceiling cup colour Ceiling cup finish Ceiling cup finish Ceiling cup fixing Cei	Efficacy (Im/w)		-	Plug details	NA	
Ceiling cup details Ceiling cup shape Ceiling cup colour Ceiling cup finish Ceiling cup fixing Ceiling cup material Ceiling cup fixing Ceiling cup	Ceiling cup / Back plate details		Supply cable total length (mm)			
Ceiling cup shape				Supply cable colour	-	
Ceiling cup colour - Supply cable length from switch to plug (mm) Ceiling cup finish - Packaging details Ceiling cup material - Unit box height (metres) 0.16 Ceiling cup fixing - Unit box length (metres) 0.17 Wall back plate dimensions (mm) D130xH25 Unit box net weight (kg) 0.75 Wall back plate colour - Unit box gross weight (kg) 0.95 Wall back plate material - Wall back plate fixing - Colour - Colo	Ceiling cup details			Chain length from ceiling cup to lampholder (mm)		
Ceiling cup finish Ceiling cup material Ceiling cup fixing D130xH25 Wall back plate shape Wall back plate colour Wall back plate finish Wall back plate fixing Wall back plate fixing Wall back plate fixing Ceiling cup fixing D130xH25 Unit box length (metres) Unit box width (metres) Unit box width (metres) Unit box net weight (kg) Unit box gross weight (kg)	Ceiling cup shape	-				
Ceiling cup material - Unit box height (metres) 0.16 Ceiling cup fixing - Unit box length (metres) 0.17 Wall back plate dimensions (mm) D130xH25 Unit box width (metres) 0.17 Wall back plate shape - Unit box net weight (kg) 0.75 Wall back plate colour - Unit box gross weight (kg) 0.95 Wall back plate finish - Unit box gross weight (kg) 0.95 Wall back plate material - Unit box gross weight (kg) 0.95	Ceiling cup colour	-		Supply cable length from switch to plug (mm)		
Ceiling cup fixing - Unit box length (metres) 0.17 Wall back plate dimensions (mm) D130xH25 Unit box width (metres) 0.17 Wall back plate shape - Unit box net weight (kg) 0.75 Wall back plate colour - Unit box gross weight (kg) 0.95 Wall back plate finish - Unit box gross weight (kg) 0.95 Wall back plate material - Wall back plate fixing - Unit box gross weight (kg) 0.95	Ceiling cup finish	-		Packaging details		
Wall back plate dimensions (mm) D130xH25 Unit box width (metres) Unit box net weight (kg) Unit box gross weight (kg) Unit box gro	Ceiling cup material	-		Unit box height (metres)	0.16	
Wall back plate shape - Unit box net weight (kg) 0.75 Wall back plate colour - Unit box gross weight (kg) 0.95 Wall back plate finish - Wall back plate material - Wall back plate fixing - Unit box gross weight (kg) 0.95	Ceiling cup fixing	-		Unit box length (metres)	0.17	
Wall back plate colour - Unit box gross weight (kg) 0.95 Wall back plate finish - Wall back plate material - Wall back plate fixing	Wall back plate dimensions (mm)	D130xH25		Unit box width (metres)	0.17	
Wall back plate finish Wall back plate material Wall back plate fixing	Wall back plate shape	-		Unit box net weight (kg)	0.75	
Wall back plate material - Wall back plate fixing -	Wall back plate colour	-		Unit box gross weight (kg)	0.95	
Wall back plate fixing -	Wall back plate finish	-				
	Wall back plate material	-				
Additional comments (Default)	Wall back plate fixing	-		7		
	Additional comments			(Default)		