


| | | | |
|-----------------------|---|--|---|
| Product number | 82530BK | Professional image / Primary image  | Technical 2D/3D Line Drawing with Measurements |
| Date: | 28/06/2023 | | |
| Product range | | | |
| Product name | Alex Outdoor Wall Upplight - Silk Black Metal & Glass, IP44 | | |
| Application | - | | |
| Barcode | 5013874157874 | | |

| Product Details | | Base Details | |
|--|---|---|------------------|
| Primary material | Aluminium | Base dimensions (mm) | |
| Secondary material | Glass | Light details | |
| Colour | Black | Primary lamp holder | E27 |
| Finish | - | Primary lamp holder number of lamps | 1 |
| Total height (mm) | 430 | Primary lamp type | GLS |
| Height (mm) | 430 | Primary lamp included | No |
| Width (mm) | 230 | Secondary lamp holder | - |
| Length (mm) | | Secondary lamp holder number of lamps | |
| Projection (mm) | 290 | Secondary lamp type | - |
| Shade/glass/diffuser colour | Clear panels | Secondary lamp included | - |
| Shade/glass/diffuser finish | - | Class | 1 (Earthed) |
| Shade/glass/diffuser material | Glass | Lumen output | |
| Shade/glass/diffuser style | - | Colour temperature (K) | - |
| Cut out (mm) | | CRI | |
| Recess depth (mm) | | Beam angle (degrees) | |
| Fire rated | (Default) | Electrical details | |
| IP rating | 44 | Primary lamp wattage | 60 |
| Bathroom zones | - | Secondary lamp wattage | |
| Tilt angle (degrees) | - | Operating voltage | 220-240V 50/60Hz |
| Height adjustable | No | Transformer/driver details | |
| Adjustable details | No | Dimmable | - |
| Max drop for ceiling fittings (mm) | | Dimming method | - |
| Minimum drop for ceiling fittings (mm) | | Switched | - |
| Energy class | N/A | Switch location | - |
| Warranty details | All Outdoor Lighting – 3 Year Guarantee | Switch type | - |
| Efficacy (lm/w) | | Plug details | NA |
| Ceiling cup / Back plate details | | Supply cable total length (mm) | |
| Ceiling cup dimensions (mm) | | Supply cable colour | - |
| Ceiling cup details | | Chain length from ceiling cup to lampholder (mm) | |
| Ceiling cup shape | - | Supply cable length from base/lampholder to switch (mm) | |
| Ceiling cup colour | - | Supply cable length from switch to plug (mm) | |
| Ceiling cup finish | - | Packaging details | |
| Ceiling cup material | - | Unit box height (metres) | 0.318 |
| Ceiling cup fixing | - | Unit box length (metres) | 0.29 |
| Wall back plate dimensions (mm) | H200 * W130 | Unit box width (metres) | 0.235 |
| Wall back plate shape | - | Unit box net weight (kg) | 1.5 |
| Wall back plate colour | - | Unit box gross weight (kg) | 1.9 |
| Wall back plate finish | - | | |
| Wall back plate material | - | | |
| Wall back plate fixing | - | | |
| Additional comments | (Default) | | |